


英管螺纹60°锥密封接头



KF2TB9-SP

90° 弯英锥管外螺纹 / 英管内螺纹 60° 外锥  
90° ELBOW BSPT MALE / BSP FEMALE 60° CONE

| 代号<br>PART NO. | 螺 纹 THREAD |            | 尺 寸 DIMENSIONS |  |      |      |    |    |  |
|----------------|------------|------------|----------------|--|------|------|----|----|--|
|                | E          | F          |                |  | A    | B    | S1 | S2 |  |
| KF2TB9-02SP    | R1/8"X28   | G1/8"X28   |                |  | 21   | 5.5  | 11 | 14 |  |
| KF2TB9-04SP    | R1/4"X19   | G1/4"X19   |                |  | 25.5 | 5.5  | 14 | 19 |  |
| KF2TB9-06SP    | R3/8"X19   | G3/8"X19   |                |  | 28.5 | 6.3  | 16 | 22 |  |
| KF2TB9-06-08SP | R3/8"X19   | G1/2"X14   |                |  | 31   | 7.5  | 19 | 27 |  |
| KF2TB9-08-06SP | R1/2"X14   | G3/8"X19   |                |  | 36   | 6.3  | 22 | 22 |  |
| KF2TB9-08SP    | R1/2"X14   | G1/2"X14   |                |  | 36   | 7.5  | 22 | 27 |  |
| KF2TB9-08-12SP | R1/2"X14   | G3/4"X14   |                |  | 37   | 10.9 | 24 | 32 |  |
| KF2TB9-12-08SP | R3/4"X14   | G1/2"X14   |                |  | 43.5 | 7.5  | 27 | 27 |  |
| KF2TB9-12SP    | R3/4"X14   | G3/4"X14   |                |  | 43.5 | 10.9 | 27 | 32 |  |
| KF2TB9-16SP    | R1"X11     | G1"X11     |                |  | 50   | 11.7 | 33 | 41 |  |
| KF2TB9-20SP    | R1.1/4"X11 | G1.1/4"X11 |                |  | 58   | 11   | 41 | 50 |  |
| KF2TB9-24SP    | R1.1/2"X11 | G1.1/2"X11 |                |  | 62.5 | 13   | 48 | 55 |  |