


英管螺纹60°锥密封接头



KF1BG

英管外螺纹60° 内锥或六角端面用组合垫密封 /
英管外螺纹O形圈
BSP MALE DOUBLE USE FOR 60° CONE SEAT OR
BONDED SEAL / BSP MALE O-RING

代 号 PART NO.	螺 纹 THREAD		O形圈 O-RING		尺 寸 DIMENSIONS				
	E	F		F端	A	B	L	S1	
KF1BG-02	G1/8"X28	G1/8"X28		O011	10	9.5	27	14	
KF1BG-04	G1/4"X19	G1/4"X19		O111	12	11	31	19	
KF1BG-04-06	G1/4"X19	G3/8"X19		O113	12	11.5	32	22	
KF1BG-06	G3/8"X19	G3/8"X19		O113	13.5	11.5	33	22	
KF1BG-06-04	G3/8"X19	G1/4"X19		O111	13.5	11	32.5	22	
KF1BG-06-08	G3/8"X19	G1/2"X14		O115	13.5	14	38.5	27	
KF1BG-08	G1/2"X14	G1/2"X14		O115	16	14	41	27	
KF1BG-08-06	G1/2"X14	G3/8"X19		O113	16	11.5	36	27	
KF1BG-08-12	G1/2"X14	G3/4"X14		O119	16	15.5	45.5	32	
KF1BG-10-08	G5/8"X14	G1/2"X14		O115	17.5	14	44.5	30	
KF1BG-12	G3/4"X14	G3/4"X14		O119	18.5	15.5	46	32	
KF1BG-12-08	G3/4"X14	G1/2"X14		O115	18.5	14	45.5	32	
KF1BG-16-08	G1"X11	G1/2"X14		O115	20.5	14	50.5	41	
KF1BG-16	G1"X11	G1"X11		O217	20.5	18	53	41	
KF1BG-16-12	G1"X11	G3/4"X14		O119	20.5	15.5	52	41	
KF1BG-20	G1.1/4"X11	G1.1/4"X11		O222	20.5	20	58.5	50	
KF1BG-24	G1.1/2"X11	G1.1/2"X11		O224	23	21.5	62.5	55	
注： F端与DIN 3852油口相配。 F end is connected with DIN 3852 port.									