



扣压式软管接头



KF29691



KF29691-W

90° 日本英管内螺纹 60° 内锥面  
90° JIS GAS FEMALE 60° CONE SEAT  
JIS B8363

| 代 号<br>PART NO.                                                                                                                                             | 螺 纹 E<br>THREAD E | 胶 管 HOSE BORE |         |  | 尺 寸 DIMENSIONS |      |       |    |    |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|---------------|---------|--|----------------|------|-------|----|----|
|                                                                                                                                                             |                   | 公称内径 DN       | 标号 DASH |  | A              | C    | H     | S1 | S2 |
| KF29691-04-04                                                                                                                                               | G1/4"X19          | 6             | 04      |  | 30             | 8    | 38    | 19 | 19 |
| KF29691-04-05                                                                                                                                               | G1/4"X19          | 8             | 05      |  | 34             | 8    | 41    | 19 | 19 |
| KF29691-06-06                                                                                                                                               | G3/8"X19          | 10            | 06      |  | 35.6           | 9    | 45.8  | 22 | 22 |
| KF29691-08-08                                                                                                                                               | G1/2"X14          | 12            | 08      |  | 41             | 12   | 53    | 27 | 27 |
| KF29691-10-10                                                                                                                                               | G5/8"X14          | 16            | 10      |  | 56.5           | 11.5 | 61    | 30 | 30 |
| KF29691-12-12                                                                                                                                               | G3/4"X14          | 20            | 12      |  | 65.5           | 13.5 | 69    | 32 | 32 |
| KF29691-16-16                                                                                                                                               | G1"X11            | 25            | 16      |  | 76.7           | 16   | 76.5  | 41 | 41 |
| KF29691-20-20W                                                                                                                                              | G1.1/4"X11        | 32            | 20      |  | 91.5           | 18.5 | 92.5  | 50 | 50 |
| KF29691-24-24W                                                                                                                                              | G1.1/2"X11        | 40            | 24      |  | 109.4          | 19   | 110.5 | 55 | 55 |
| KF29691-32-32W                                                                                                                                              | G2"X11            | 50            | 32      |  | 131.8          | 23   | 133.8 | 70 | 70 |
| 注：1. 表中代号用于编织软管。 2. 如需用于缠绕软管代号改为 29692-xx-xx。<br>Note: 1.For use with braided hoses. 2.If use with spiral hoses, hose fitting series number is 29692-xx-xx. |                   |               |         |  |                |      |       |    |    |