


扣压式软管接头



KF22691K

90° 英管短身内螺纹 60° 外锥面
90° BSP COMPACT FEMALE 60° CONE

代 号 PART NO.	螺 纹 E THREAD E	胶 管 HOSE BORE		尺 寸 DIMENSIONS				
		公称内径 DN	标号 DASH	A	C	H	S1	S2
KF22691K-04-04	G1/4"X19	6	04	17.5	5.5	18.5	11	19
KF22691K-06-04	G3/8"X19	6	04	20	6.3	24	16	22
KF22691K-06-05	G3/8"X19	8	05	20	6.3	24	16	22
KF22691K-06-06	G3/8"X19	10	06	20	6.3	24	16	22
KF22691K-08-06	G1/2"X14	10	06	23	7.5	28.5	19	27
KF22691K-08-08	G1/2"X14	12	08	23.5	7.5	28.5	19	27
KF22691K-10-10	G5/8"X14	16	10	24.5	9.5	30.5	22	30
KF22691K-12-12	G3/4"X14	20	12	27.5	10.9	33	27	32
KF22691K-16-16	G1"X11	25	16	43	11.7	38.5	33	41
注： 1. 表中代号用于编织软管。 2. 如需用于缠绕软管代号改为 22692K-xx-xx。 Note: 1.For use with braided hoses. 2.If use with spiral hoses, hose fitting series number is 22692K-xx-xx.								