


扣压式软管接头



KF26791K

90° 美制短身 JIC 内螺纹 74° 内锥面
90° JIC COMPACT FEMALE 74° CONE SEAT
SAE J514

代 号 PART NO.	螺 纹 E THREAD E	胶 管 HOSE BORE		尺 寸 DIMENSIONS				
		公称内径 DN	标号 DASH	A	C	H	S1	S2
KF26791K-04-04	7/16"X20	6	04	17.5	9	18	11	15
KF26791K-06-04	9/16"X18	6	04	20	10.5	20.5	14	19
KF26791K-06-06	9/16"X18	10	06	20	10.5	20.5	16	19
KF26791K-08-06	3/4"X16	10	06	23	11	25	19	24
KF26791K-08-08	3/4"X16	12	08	23.5	11	25	22	24
KF26791K-10-08	7/8"X14	12	08	25	13	27	22	27
KF26791K-10-10	7/8"X14	16	10	25	13	27	22	27
KF26791K-12-12	1.1/16"X12	20	12	29	15	31	27	32
KF26791K-16-16	1.5/16"X12	25	16	43	16	34.3	33	41
注：1. 表中代号用于编织软管。 2. 如需用于缠绕软管代号改为 26792K-xx-xx。 Note: 1.For use with braided hoses. 2.If use with spiral hoses, hose fitting series number is 26792K-xx-xx.								