




扣压式软管接头



KF24241



KF24241-T



KF24241-W

45° 美制ORFS内螺纹平面
45° ORFS FEMALE FLAT SEAT
ISO 12151-1--SAE J516

代 号 PART NO.	螺 纹 E THREAD E	胶 管 HOSE BORE			尺 寸 DIMENSIONS			
		公称内径 DN	标号 DASH		A	H	C	S2
KF24241-04-04	9/16"X18	6	04		45.5	23.4	8.5	19
KF24241-04-05	9/16"X18	8	05		47.6	24.3	8.5	19
KF24241-04-06	9/16"X18	10	06		49.2	24.9	8.5	19
KF24241-06-04T	11/16"X16	6	04		39.5	17.4	10	22
KF24241-06-05T	11/16"X16	8	05		42.3	19	10	22
KF24241-06-06	11/16"X16	10	06		51.3	27.1	10	22
KF24241-08-06T	13/16"X16	10	06		44.6	20.3	11	27
KF24241-08-08	13/16"X16	12	08		65.7	30.7	11	27
KF24241-08-10	13/16"X16	16	10		76.5	31.7	11	27
KF24241-10-08T	1"X14	12	08		58.2	23.3	13.5	30
KF24241-10-10	1"X14	16	10		79.2	34.9	13.5	30
KF24241-12-08T	1.3/16"X12	12	08		58.2	23.3	15	36
KF24241-12-10T	1.3/16"X12	16	10		68.2	23.9	15	36
KF24241-12-12	1.3/16"X12	20	12		87	39.5	15	36
KF24241-12-16	1.3/16"X12	25	16		95.3	41	15	36
KF24241-16-12T	1.7/16"X12	20	12		74	29.6	14.8	41
KF24241-16-14T	1.7/16"X12	22	14		78.7	28.5	14.8	41
KF24241-16-16T	1.7/16"X12	25	16		84.1	29.7	14.8	41
KF24241-20-16T	1.11/16"X12	25	16		84.1	29.7	15	50
KF24241-20-20W	1.11/16"X12	32	20		111.2	49	15	50
KF24241-24-20T	2"X12	32	20		94.5	33.8	14.8	60
KF24241-24-24T	2"X12	40	24		108.5	37.7	14.8	60

注： 1. 表中代号用于编织软管。

2. 如需用于缠绕软管代号改为 24242-xx-xx。

Note: 1.For use with braided hoses.

2.If use with spiral hoses, hose fitting series number is 24242-xx-xx.